

# ROCK GRIP IND4 (ECH)

|                     |                                      |
|---------------------|--------------------------------------|
| <b>TIRE SIZE</b>    | 16.00 - 25                           |
| <b>UM</b>           | IS STANDARD                          |
| <b>CONSTRUCTION</b> | ❖ BIAS                               |
| <b>MACHINERY</b>    | MOVIMENTATORE PER CONTAINER<br>VUOTI |
| <b>VERSIONE</b>     | PORT INDUSTRIAL                      |
| <b>TIRE TYPE</b>    | TL                                   |



## DIMENSIONI IS STANDARD

|                 |           |                 |           |
|-----------------|-----------|-----------------|-----------|
| <b>OD (MM)</b>  | 1525      | <b>RIM ALT</b>  | 13.00/2.0 |
| <b>SLR (MM)</b> | 699       | <b>PR</b>       | 32        |
| <b>RC (MM)</b>  | 4514      | <b>TRA CODE</b> | IND4      |
| <b>RIM REC</b>  | 11.25/2.0 |                 |           |

## LOAD CAPACITY (KG/TIRE)

|                   |              |
|-------------------|--------------|
| <b>KM/H / BAR</b> | <b>10.00</b> |
| 10                | 16875        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.