


AGRIMAX V-FLECTO



| | |
|---------------------|--|
| TIRE SIZE | VF 650/85 R 38 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | HOCHLEISTUNGSTRAKTOR / TRACTOR |
| VERSION | SPECIAL |
| TIRE TYPE | TL |
| LI/SS | 182 D |

ABMESSUNGEN US STANDARD

| | | | |
|-----------------|----------|----------------|------------------|
| USA-CODE | 94513543 | RC (IN) | 240.9 |
| SW (IN) | 26.4 | RIM REC | DW 23 B |
| OD (IN) | 81.5 | RIM ALT | DW 20 B; DW 21 B |
| SLR (IN) | 34.9 | ECE | E11-106R-0010579 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 |
|---------------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 8520 | 9890 | 11250 | 12790 | 14150 | 15510 | 17050 |
| FROM 40 TO 25 | 9370 | 10870 | 12370 | 14050 | 15550 | 17050 | 18740 |
| 20 | 9560 | 11080 | 12610 | 14330 | 15860 | 17380 | 19110 |
| 12 | 9740 | 11300 | 12850 | 14620 | 16170 | 17720 | 19490 |
| 5 | 10310 | 11950 | 13600 | 15450 | 17110 | 18750 | 20610 |
| UPTO 20 CYC | 10630 | 12320 | 14030 | 15940 | 17650 | 19340 | 21260 |
| UPTO 10 CYC | 12690 | 14720 | 16740 | 19040 | 21060 | 23090 | 25380 |
| UPTO 5CYC | 13910 | 16130 | 18350 | 20870 | 23080 | 25310 | 27820 |
| 5 HT | 9560 | 11080 | 12610 | 14330 | 15860 | 17380 | 19110 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.