


# MULTIMAX MP 527



<b>TIRE SIZE</b>	500/70 R 24 IND
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE / CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	164 A8/B

## DIMENSIONS US STANDARD

<b>CODE USA</b>	94052233	<b>RC (IN)</b>	158.2
<b>SW (IN)</b>	19.8	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	51.6	<b>RIM ALT</b>	DW 15 L ; DW 18 L
<b>SLR (IN)</b>	23.5	<b>ECE</b>	E4-106R-002658

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	5290	6280	7160	8160	9150	9810	11020	-	-
25	5290	6280	7160	8160	9150	9810	11020	-	-
20	5670	6720	7670	8730	9800	10500	11790	-	-
15	5870	6980	7960	9060	10160	10890	11230	-	-
5 CYC.	6450	7940	9350	10750	12230	13320	15050	15870	16530
STATIC	9890	12170	14330	16480	18760	20410	23070	24340	25350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.