


EARTHMAX SR 53

| | |
|--------------|--|
| TIRE SIZE | 29.5 R 29 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | БУЛЬДОЗЕР / ПОГРУЗЧИК / НИЗКОПРОФИЛЬНЫЙ САМОСВАЛ |
| VERSION | CUT RESISTANT COMPOUND |
| TIRE TYPE | TL |
| LI/SS | 218 A2 |



РАЗМЕРЫ IS STANDARD

| | | | |
|----------|-----------|-------------|-----------|
| OD (MM) | 2015 | RIM ALT | 24.00/3.5 |
| SLR (MM) | 905 | TRA CODE | L5 |
| RC (MM) | 6059 | STAR RATING | ★★ |
| RIM REC | 25.00/3.5 | | |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 5.25 | 5.50 | 5.75 | 6.00 | 6.25 | 6.50 |
|------------|-------|-------|-------|-------|-------|-------|
| 10 | 20000 | 20600 | 21200 | 22400 | 23000 | 23600 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.