


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>340/65 R 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VENDIMIADORA / TRACTOR / COSECHADORA
<b>VERSIÓN</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	113 A8/B



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	343	<b>RIM REC</b>	W 11
<b>OD (MM)</b>	899	<b>RIM ALT</b>	W 10 ; W 12
<b>SLR (MM)</b>	400	<b>ECE</b>	E4-106R-001816
<b>RC (MM)</b>	2667	<b>SRI</b>	425

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
50	645	760	865	970	1060	1150
40	645	760	865	970	1060	1150
30	695	820	930	1040	1140	1235
10 LT	870	1020	1160	1300	1425	1545
10 HT	695	820	930	1040	1140	1235

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.