

FLOTATION 558

| | |
|---------------------------|---|
| TIRE SIZE | 500/45 - 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | |
| MACHINERY | BALER / HAY HARVESTER / TANKER / TRAILER / HARVESTER / IMPLEMENTS |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 146 A8/142 B |
| LI/SS FREE ROLLING | 158 A8/154 B |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|-----------------|
| USA CODE | 94058518 | RC (IN) | 124.7 |
| SW (IN) | 19.7 | RIM REC | AG 16.00 |
| OD (IN) | 41.1 | ECE | E11-106R-005353 |
| SLR (IN) | 18.5 | PR | 20 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 62 | 64 | 65 |
|-----------|-------|-------|-------|
| 5 FR | 12780 | 12950 | 13120 |
| 10 FR | 11500 | 11650 | 11810 |
| 20 FR | 10220 | 10360 | 10490 |
| 25 FR | 9130 | 9250 | 9370 |
| 30 FR | 8210 | 8320 | 8270 |
| 5 DW | 9020 | 9140 | 9260 |
| 10 DW | 8110 | 8220 | 8330 |
| 20 DW | 7210 | 7310 | 7410 |
| 25 DW | 6440 | 6530 | 6610 |
| 30 DW | 5800 | 5870 | 5840 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.