


# AGRIMAX RT 765

	<b>260/70 R 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRAKTÖR / UYGULAMALI MAKINE / ÜZÜM HASAT MAKINESİ / BIÇERDÖVER
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	109 A8/B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94021888	<b>RC (IN)</b>	89.9
<b>SW (IN)</b>	10.2	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	30.3	<b>RIM ALT</b>	W 8 L ; W 9 L
<b>SLR (IN)</b>	13.6	<b>ECE</b>	E4-106R-000610

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1070	1230	1410	1600	1770	1960	2120	2270
25	1070	1230	1410	1600	1770	1960	2120	2270
20	1150	1320	1520	1710	1910	2110	2270	2440
5 LT	1430	1650	1900	2140	2380	2620	2830	3040
5 HT	1150	1320	1520	1710	1910	2110	2270	2440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.