

# AS 504

<b>TIRE SIZE</b>	<b>16.0/70 - 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	139 A8
<b>LI/SS FREE ROLLING</b>	151 A8



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	418	<b>RIM REC</b>	13
<b>OD (MM)</b>	1097	<b>RIM ALT</b>	12 SDC; 14; 13 SDC
<b>SLR (MM)</b>	487	<b>ECE</b>	E11-106R-004610
<b>RC (MM)</b>	3214	<b>PR</b>	12

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.00
10 FR	4830
25 FR	4105
30 FR	3865
40 FR	3450
10 DW	3400
25 DW	2890
30 DW	2720
40 DW	2430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.