


AGRIMAX RT 855

TIRE SIZE	340/85 R 28
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	BESPRUTNINGSBIL / SKÖRDEMASKIN FÖR VINGÅRD / TRAKTOR / SKÖRDEMASKIN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	139 A8/B



DIMENSIONER US STANDARD

USA CODE	94073269	RC (IN)	156.0
SW (IN)	13.9	RIM REC	W 12
OD (IN)	51.8	RIM ALT	W 11
SLR (IN)	23.7	ECE	E11-106R-008233

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	47
30	2090	2470	2840	3160	3540	3860	4230	4560	4980	5360
25	2090	2470	2840	3160	3540	3860	4230	4560	4980	5360
20	2250	2650	3050	3390	3790	4140	4540	4880	5350	5740
5 LT	2810	3310	3810	4240	4750	5180	5690	6120	6690	7190
5 HT	2250	2650	3050	3390	3790	4140	4540	4880	5350	5740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.