


# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>650/65 R 42</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VINEYARD HARVESTER / TRACTOR / HARVESTER
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	165 D ; 168 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	645	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1913	<b>RIM ALT</b>	DW 21 B ; DW 23 B
<b>SLR (MM)</b>	878	<b>ECE</b>	E4-106R-000625
<b>RC (MM)</b>	5810	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
<b>65</b>	2475	2885	3245	3605	3970	4275	4740	5150
<b>50</b>	2600	3030	3410	3790	4170	4495	4980	5410
<b>40</b>	2690	3140	3530	3920	4315	4650	5155	5600
<b>30</b>	2845	3320	3735	4150	4565	4920	5455	5925
<b>10 LT</b>	3315	3870	4355	4835	5320	5735	6355	6905
<b>10 HT</b>	2845	3320	3735	4150	4565	4920	5455	5925

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.