


AGRIMAX SPARGO

| | |
|--------------|--|
| TIRE SIZE | VF 380/90 R 46 CFO |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRATTORE |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 175 D |



DIMENSIONI IS STANDARD

| | | | |
|----------|------|---------|--------------------|
| SW (MM) | 390 | RIM REC | DW 13 A |
| OD (MM) | 1852 | RIM ALT | W 13 A ; DW 12 |
| SLR (MM) | 848 | ECE | E11-106R-007527-01 |
| RC (MM) | 5611 | SRI | 875 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.4 | 1.6 | 1.8 | 2 | 2.2 | 2.4 | 2.6 | 2.8 | 3 | 3.2 | 3.4 | 3.6 | 3.8 | 4 | 4.2 | 4.4 | 4.6 |
|---------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 70 | 2835 | 3190 | 3485 | 3665 | 3480 | 3960 | 4080 | 4315 | 4495 | 4670 | 4850 | 5025 | 5145 | 5320 | 5440 | 5675 | 5915 | 6210 |
| FROM 65 TO 40 | 3120 | 3510 | 3835 | 4030 | 4225 | 4355 | 4485 | 4745 | 4940 | 5135 | 5330 | 5525 | 5655 | 5850 | 5980 | 6240 | 6500 | 6900 |
| 30 | 3180 | 3580 | 3910 | 4110 | 4305 | 4440 | 4570 | 4835 | 5035 | 5235 | 5435 | 5635 | 5765 | 5965 | 6095 | 6360 | 6630 | 7040 |
| 20 | 3240 | 3650 | 3985 | 4190 | 4390 | 4525 | 4660 | 4930 | 5135 | 5340 | 5540 | 5745 | 5880 | 6080 | 6215 | 6485 | 6760 | 7180 |
| 10* | 3430 | 3860 | 4215 | 4430 | 4645 | 4790 | 4930 | 5215 | 5430 | 5645 | 5860 | 6075 | 6220 | 6435 | 6575 | 6860 | 7150 | 7590 |
| UPTO 15 CYC. | 4230 | 4760 | 5200 | 5465 | 5730 | 5905 | 6080 | 6430 | 6695 | 6960 | 7225 | 7490 | 7665 | 7930 | 8105 | 8460 | 8810 | 9350 |
| UPTO 30 CYC. | 3545 | 3990 | 4355 | 4580 | 4800 | 4950 | 5095 | 5390 | 5610 | 5835 | 6055 | 6275 | 6425 | 6645 | 6795 | 7090 | 7385 | 7835 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.