


# AS 509

<b>TYRE SIZE</b>	<b>550/45 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	IMPLEMENT MACHINERY / TRAILER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	141 A8/137 B
<b>LI/SS FREE ROLLING</b>	153 A8/149 B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94064878	<b>RC (IN)</b>	128.0
<b>SW (IN)</b>	21.3	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	41.9	<b>ECE</b>	E11-106R-006445
<b>SLR (IN)</b>	18.9	<b>PR</b>	12

## LOAD CAPACITY (LBS/TYRE)

MPH / PSI	22	26	30
5 FR	9260	10300	11260
10 FR	8330	9260	10140
20 FR	7410	8230	9020
25 FR	6610	7350	8050
30 FR	5950	6610	7160
5 DW	6530	7260	7950
10 DW	5870	6540	7150
20 DW	5220	5820	6360
25 DW	4660	5190	5680
30 DW	4200	4670	5070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.