

# AGRIMAX SPARGO

<b>TIRE SIZE</b>	<b>VF 480/95 R 50</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	181 D



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94075638	<b>RC (IN)</b>	260.1
<b>SW (IN)</b>	18.9	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	85.9	<b>RIM ALT</b>	DW 15 L
<b>SLR (IN)</b>	39.0	<b>ECE</b>	E11-106R-0010083

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	17	20	23	26	29	32	35	38	41	44	46
45	8920	9930	11100	12120	12790	13290	13790	14300	14970	15650	16150	16830
FROM 40 TO 25	9650	10730	12010	13100	13830	14370	14920	15470	16200	16920	17460	18190
20	9840	10940	12240	13360	14110	14650	15220	15780	16520	17260	17820	18560
12	10040	11160	12480	13630	14390	14940	15510	16090	16840	17600	18170	18920
5	10610	11800	13200	14410	15220	15800	16410	17010	17810	18610	19220	20010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.