


TR 882

| | |
|---------------------------|--|
| TYRE SIZE | 400/60 - 15.5 |
| UM | IS STANDARD |
| CONSTRUCTION |  BIAS |
| MACHINERY | HAY HARVESTER / IMPLEMENT MACHINERY / TRAILER / IMPLEMENTS / TRAILER |
| VERSION | ARAMID BELTED |
| TYRE TYPE | TL |
| LI/SS DRIVE WHEEL | 132 A8 |
| LI/SS FREE ROLLING | 145 A8 |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 400 | RIM REC | AG 13.00 |
| OD (MM) | 875 | ECE | E11-106R-004331 |
| SLR (MM) | 378 | PR | 14 |
| RC (MM) | 2605 | SRI | 410 |

LOAD CAPACITY (KG/TYRE)

| KM/H / BAR | 3.60 |
|------------|------|
| 10 FR | 4060 |
| 25 FR | 3450 |
| 30 FR | 3250 |
| 40 FR | 2900 |
| 10 DW | 2800 |
| 25 DW | 2380 |
| 30 DW | 2240 |
| 40 DW | 2000 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.