

# TR 313

<b>TIRE SIZE</b>	<b>31X15.50 - 15</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / МАШИНА ДЛЯ СБОРА ФРУКТОВ / ТРАНШЕЙНЫЙ ЭКСКАВАТОР / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	370	<b>RIM REC</b>	13 LB
<b>OD (MM)</b>	780	<b>ECE</b>	E4-106R-002208
<b>SLR (MM)</b>	342	<b>PR</b>	8
<b>RC (MM)</b>	2233		

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>3.10</b>
50	1250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.