


# MULTIMAX MP 515

|              |  |
|--------------|--|
| TIRE SIZE    | 445/65 R 22.5 MPT  |
| UM           | US STANDARD  |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | VEICULO UNIVERSAL / CAMIÃO DE FERTILIZANTES  |
| VERSÃO       | STANDARD   |
| TIRE TYPE    | TL   |
| LI/SS        | 160 G  |



## DIMENSÕES US STANDARD

|            |          |         |                 |
|------------|----------|---------|-----------------|
| CÓDIGO USA | 94057207 | RC (IN) | 139.1           |
| SW (IN)    | 17.5     | RIM REC | 13              |
| OD (IN)    | 45.3     | RIM ALT | 14              |
| SLR (IN)   | 20.7     | ECE     | E11-54R-0017868 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23   | 29   | 36   | 44   | 51   | 58   | 65   | 87    |
|-----------|------|------|------|------|------|------|------|-------|
| 55        | 3840 | 4540 | 5310 | 6060 | 6780 | 7470 | 8380 | 9920  |
| 40        | 4170 | 4930 | 5760 | 6580 | 7360 | 8100 | 8820 | 10770 |
| 25        | 4420 | 5210 | 6110 | 6980 | 7800 | 8600 | 9350 | 11410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.