

# EM 936

|                     |                                      |
|---------------------|--------------------------------------|
| <b>TIRE SIZE</b>    | <b>8.25 - 20</b>                     |
| <b>UM</b>           | IS STANDARD                          |
| <b>CONSTRUCTION</b> | ⊠ BIAS                               |
| <b>MACHINERY</b>    | EXCAVATOR / ÎNCĂRCĂTOR<br>TELESCOPIC |
| <b>VERSION</b>      | STANDARD                             |
| <b>TIRE TYPE</b>    | TT                                   |
| <b>LI/SS</b>        | 133 B                                |



## DIMENSIUNI IS STANDARD

|                 |      |                 |          |
|-----------------|------|-----------------|----------|
| <b>OD (MM)</b>  | 980  | <b>RIM ALT</b>  | 6.0; 7.0 |
| <b>SLR (MM)</b> | 467  | <b>PR</b>       | 14       |
| <b>RC (MM)</b>  | 2970 | <b>TRA CODE</b> | E2       |
| <b>RIM REC</b>  | 6.5  |                 |          |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>6.75</b> |
| 50                | 2060        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.