


AGRIMAX RT 600

| | |
|---------------------|--|
| TIRE SIZE | 1050/50 R 32 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAȘINĂ DE RECOLTARE / MAȘINĂ DE ÎMPRĂȘTIAT / TRACTOR / MAȘINI DE IMPLEMENTARE |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 184 A8 ; 181 B |



DIMENSIUNI US STANDARD

| | | | |
|-----------------|----------|----------------|----------------------|
| USA CODE | 94040728 | RC (IN) | 224.4 |
| SW (IN) | 41.7 | RIM REC | 36.0 VA (multipiece) |
| OD (IN) | 73.3 | ECE | E4-106R-000813 |
| SLR (IN) | 32.5 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 20 | 23 | 29 | 35 | 41 | 46 | 49 | 55 |
|-----------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 8190 | 9280 | 11640 | 12920 | 14370 | 15460 | 16920 | 18190 | - | - |
| 25 | 8930 | 10120 | 12700 | 14090 | 15670 | 16860 | 18450 | 19840 | - | - |
| 20 | 9560 | 10840 | 13590 | 15080 | 16780 | 18050 | 19750 | 21230 | - | - |
| 5 LT | 11970 | 13570 | 17020 | 18880 | 21010 | 22610 | 24730 | 26590 | - | - |
| 5 HT | 9560 | 10840 | 13590 | 15080 | 16780 | 18050 | 19750 | 21230 | - | - |
| 5 CYC | - | 15010 | 19230 | 21090 | 24460 | 25470 | 27880 | 29970 | 31290 | 33730 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.