



IS standard



GROWING TOGETHER

AIROMAX

RADIAL CRANE TIRES

AM 543



PRODUCT DATA SHEET



Radial



AIROMAX AM 543

RADIAL CRANE TIRES

AIROMAX AM 543 is the ideal tire for construction applications with cranes. It shows outstanding traction and high stability. As crane tires are subject to particular stress and extreme usage conditions, AIROMAX AM 543 has been designed for providing excellent heat resistance. Besides, it is suitable for all operations requiring a high level of handling.

Technologies



High Speed



All Steel

Performance



Durability



High Load Capacity



Traction

	Tire size	Type	STAR RATING	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 24"	385/95 R 24 (14.00 R 24)	TT	-	170 E	STD	375	1355	627	4156	10.00 W	-
Ø 25"	385/95 R 25 (14.00 R 25)	TL	-	170 E	STD	375	1355	627	4156	10.00/1.5	-
	445/95 R 25 (16.00 R 25)	TL	-	177 E	STD	435	1480	670	4502	11.25/2.0	11.00/1.7 CR ; 11.00/1.7 CRL

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference