

# FS 216

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>28L - 26</b>  |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | COSECHADORA FORESTAL /<br>AUTOCARGADORA  |
| <b>VERSIÓN</b>      | STEEL BELTED   |
| <b>TIRE TYPE</b>    | TL   |



## DIMENSIONES IS STANDARD

|                 |      |                 |                  |
|-----------------|------|-----------------|------------------|
| <b>SW (MM)</b>  | 720  | <b>RIM REC</b>  | DW 25 A; DW 25 B |
| <b>OD (MM)</b>  | 1660 | <b>ECE</b>      | E11-106R-006733  |
| <b>SLR (MM)</b> | 742  | <b>PR</b>       | 20               |
| <b>RC (MM)</b>  | 4912 | <b>TRA CODE</b> | LS2              |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 2.80 | 2.40 |
|------------|------|------|
| 10         | 7300 | -    |
| 30         | -    | 5150 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.