

MULTIMAX MP 513

| | |
|---------------------|---|
| TIRE SIZE | 495/70 R 24 MPT |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ / ТЕХНИКА ДЛЯ ВНЕСЕНИЯ УДОБРЕНИЙ / УНИВЕРСАЛЬНЫЙ АВТОМОБИЛЬ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 155 G |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|--------------------------|
| USA CODE | 94035908 | RC (IN) | 156.5 |
| SW (IN) | 19.6 | RIM REC | W 16 L |
| OD (IN) | 51.3 | RIM ALT | DW 15 L; DW 16 L; W 15 L |
| SLR (IN) | 23.1 | ECE | E4-54R-0029057 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 23 | 29 | 36 | 44 | 51 |
|-----------|------|------|------|------|------|
| 55 | 4360 | 5160 | 6260 | 7160 | 8550 |
| 40 | 4740 | 5600 | 6800 | 7780 | 9270 |
| 25 | 5030 | 5940 | 7210 | 8240 | 9830 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.