

TR 135



TR 135



TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning proprieties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.



	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø16"	12.4 - 16	93 A8	W 11	W 9 9 W 10	12.8	37.8	17.0	112.3	-	STD
	12.4 - 16	107 A8	W 11	W 9 9 W 10	12.8	37.8	17.0	112.3	-	STD
Ø20"	9.5 - 20	104 A8	W 8	W 7	9.4	37.6	17.9	113.7	-	HD
	8.00 - 20	107 A8	5.50 F	-	8.9	38.0	17.6	111.7	-	STD
	12.4 - 20	112 A8	W 11	W 9 9 W 10 11	12.8	42.3	19.7	124.4	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
11.2 - 20	107 A8	W 10	W 9 9	11.5	40.2	18.3	121.1	-	STD
10.00 - 20	152 A2	7.5	-	11.0	42.3	19.5	124.4	-	STD
9.5 - 20	104 A8	W 8	W 7	9.4	37.6	17.9	113.7	-	STD
8.00 - 20	101 A8	5.50 F	-	8.9	38.0	17.6	111.7	-	STD
9.5 - 20	99 A8	W 8	W 7	9.4	37.6	17.5	113.4	-	STD
12.4 - 20	112 A8	W 11	W 9 9 W 10 11	12.8	42.3	19.7	124.4	-	HD
Ø24"	12.4 - 24	124 A8	W 11 W 9 W 10	12.4	45.7	21.4	140.7	550	STD
	13.6 - 24	120 A8	W 12 W 11	14.0	48.0	22.1	145.6	-	STD
	8.3 - 24	96 A8	W 7 W 6	8.3	39.2	18.5	117.5	-	STD
	13.6 - 24	120 A8	W 12 W 11	14.0	48.0	22.1	145.6	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
12.4 - 24	118 A8	W 11	W 9 W 10	12.4	45.7	20.9	136.9	550	HD
11.2 - 24	113 A8	W 10	W 9	11.2	43.5	20.0	130.0	525	HD
14.9 - 24	132 A8	W 13	W 12 W 11	14.9	49.8	22.7	151.1	600	STD
12.4 - 24	122 A8	W 11	W 9 W 10	12.4	45.7	21.4	140.7	550	STD
8.3 - 24	101 A8	W 7	W 6	8.3	39.2	18.5	117.5	-	HD
11.2 - 24	116 A8	W 10	W 9	11.2	43.5	20.4	133.8	525	HD
13.6 - 24	126 A8	W 12	W 11	14.0	48.0	22.1	145.6	-	HD
16.9 - 24	132 A8	W 15 L	W 14 L	16.9	52.6	24.1	154.5	-	STD
14.9 - 24	132 A8	W 13	W 12 W 11	14.9	49.8	22.7	151.1	600	STD
12.4 - 24	118 A8	W 11	W 9 W 10	12.4	45.7	21.4	140.7	550	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
14.9 - 24	128 A8	W 13	W 11 W 12	14.9	49.8	22.7	151.1	600	HD
11.2 - 24	106 A8	W 10	W 9	11.2	43.5	20.4	133.8	525	STD
16.9 - 24	136 A8	W 15 L	W 14 L	16.9	52.6	23.66	160.43	-	HD
11.2 - 24	116 A8	W 10	W 9	11.2	43.5	20.4	133.8	525	HD
9.5 - 24	112 A8	W 8	W 7	9.5	41.7	19.8	127.3	-	STD
14.9 - 24	124 A8	W 13	W 12 W 11	14.9	49.8	22.7	151.1	600	STD
14.9 - 24	124 A8	W 13	W 12 W 11	14.9	49.8	22.4	148.4	600	HD
8.3 - 24	101 A8	W 7	W 6	8.3	39.2	18.7	121.1	-	STD
16.9 - 24	129 A8	W 15 L	W 14 L	16.9	52.6	24.1	154.5	-	HD
14.9 - 24	132 A8	W 13	W 12 W 11	14.9	49.8	22.7	151.1	600	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
11.2 - 24	113 A8	W 10	W 9	11.2	43.5	20.4	133.8	25	STD
12.4 - 24	124 A8	W 11	W 9 W 10	12.4	45.7	21.4	140.7	550	SPL
14.9 - 24	124 A8	W 13	W 12 W 11	14.9	49.8	22.7	151.1	600	STD
14.9 - 24	124 A8	W 13	W 11 W 12	14.9	49.8	22.4	148.4	600	HD
11.2 - 24	113 A8	W 10	W 9	11.2	43.5	20.4	133.8	525	STD
13.6 - 24	120 A8	W 12	W 11	14.0	48.0	22.1	145.6	-	HD
12.4 - 24	118 A8	W 11	W 9 W 10	12.4	45.7	21.4	138.7	550	STD
16.9 - 24	129 A8	W 15 L	W 14 L	16.9	52.6	24.1	154.5	-	STD
9.5 - 24	112 A8	W 8	W 7	9.5	41.7	19.8	127.3	-	HD
13.6 - 24	126 A8	W 12	W 11	14.0	48.0	22.1	145.6	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
16.9 - 24	132 A8	W 15 L	W 14 L	16.9	52.6	24.1	154.5	-	STD
9.5 - 24	108 A8	W 8	W 7	9.5	41.7	19.8	127.3	-	HD
9.5 - 24	108 A8	W 8	W 7	9.5	41.7	19.8	127.3	-	STD
8.3 - 24	107 A8	W 7	W 6	8.3	39.2	18.5	117.5	-	HD
16.9 - 24	129 A8	W 15 L	W 14 L	16.9	52.6	24.1	154.5	-	STD
12.4 - 24	111 A8	W 11	W 9 W 10	12.4	45.7	21.4	140.7	550	STD
12.4 - 24	118 A8	W 11	W 9 W 10	12.4	45.7	20.9	136.9	550	HD
9.5 - 24	102 A8	W 8	W 7	9.5	41.7	19.8	127.3	-	STD
12.4 - 24	124 A8	W 11	W 9 W 10	12.4	45.7	21.4	140.7	550	STD
Ø26"	14.9 - 26	125 A8	W 13 W 11 W 12	14.8	51.8	23.6	155.4	-	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
23.1 - 26	149 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	STD
23.1 - 26	157 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	DB
23.1 - 26	155 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	DB
23.1 - 26	149 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	STD
16.9 - 26	133 A8	W 15 L	W 14 L	16.9	54.3	24.6	164.7	-	STD
23.1 - 26	149 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	DB
16.9 - 26	136 A8	W 15 L	W 14 L	16.9	54.3	24.6	164.7	-	STD
23.1 - 26	155 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	STD
16.9 - 26	133 A8	W 15 L	W 14 L	16.9	54.3	24.6	164.7	-	STD
23.1 - 26	155 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
23.1 - 26	155 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	STD
14.9 - 26	132 A8	W 13	W 11 W 12	14.8	51.8	23.6	155.4	-	STD
23.1 - 26	152 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	STD
14.9 - 26	125 A8	W 13	W 11 W 12	14.8	51.8	23.6	155.4	-	STD
23.1 - 26	155 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	DB HD
23.1 - 26	149 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	DB
Ø28"	14.9 - 28	121 A8	W 13 W 11 W 12	14.9	53.7	25.0	164.2	650	STD
	11.2 - 28	114 A8	W 10 W 9	11.2	47.4	22.2	139.5	575	STD
	9.5 - 28	104 A8	W 8 W 7	9.3	45.5	21.6	140.0	-	STD
	13.6 - 28	130 A8	W 12 W 11	13.6	51.6	23.9	153.9	625	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
8.3 - 28	104 A8	W 7	W 6	8.4	43.5	20.4	131.8	-	STD
14.9 - 28	133 A8	W 13	W 11 W 12	14.9	53.7	25.0	164.2	650	STD
18.4 - 28	144 A8	W 16 L	W 15 L	18.4	59.1	27.2	173.7	-	STD
14.9 - 28	135 A8	W 13	W 11 W 12	14.9	53.7	25.0	164.2	650	STD
12.4 - 28	127 A8	W 11	W 9 W 10	12.8	49.6	23.0	152.6	600	STD
14.9 - 28 (28)	126 A8	W 13	W 11 W 12	14.9	53.7	25.0	164.2	650	STD
12.4 - 28	120 A8	W 11	W 9 W 10	12.8	49.6	23.0	152.6	600	HD
14.9 - 28	133 A8	W 13	W 11 W 12	14.9	53.7	25.0	164.2	650	HD
11.2 - 28	119 A8	W 10	W 9	11.2	47.4	22.2	139.5	575	STD
9.5 - 28	110 A8	W 8	W 7	9.3	45.5	21.6	140.0	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
13.6 - 28	133 A8	W 12	W 11	13.6	51.6	23.9	153.9	625	STD
14.9 - 28	126 A8	W 13	W 11 W 12	14.9	53.7	25.0	164.2	650	HD
8.3 - 28	99 A8	W 7	W 6	8.4	43.5	20.4	131.8	-	STD
14.9 - 28	126 A8	W 13	W 11 W 12	14.9	53.7	25.0	164.2	650	STD
13.6 - 28	122 A8	W 12	W 11	13.6	51.6	23.9	153.9	625	STD
13.6 - 28	122 A8	W 12	W 11	13.6	51.6	23.9	158.4	625	HD
12.4 - 28	120 A8	W 11	W 9 W 10	12.8	49.6	23.0	152.6	600	STD
12.4 - 28	113 A8	W 11	W 9 W 10	12.8	49.6	23.0	152.6	600	STD
12.4 - 28	123 A8	W 11	W 9 W 10	12.8	49.6	23.0	152.6	600	STD
11.2 - 28	114 A8	W 10	W 9	11.2	47.4	22.2	139.5	575	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
	18.4 - 28	134 A8	W 16 L	W 15 L	18.4	59.1	27.2	173.7	-	STD
Ø30"	18.4 - 30	145 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	STD
	23.1 - 30	160 A8	DW 20 B DW 20 A	-	23.6	66.9	30.4	205.4	-	DB
	18.4 - 30	150 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	STD
	18.4 - 30	147 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	STD
	9.5 - 30	105 A8	W 8	W 7	9.5	47.2	22.3	138.9	-	STD
	16.9 - 30	136 A8	W 15 L	W 14 L	16.9	58.5	26.7	178.5	700	STD
	23.1 - 30	151 A8	DW 20 B DW 20 A	-	23.6	66.9	31.4	198.7	-	STD
	16.9 - 30 (14 - 30)	143 A8	W 15 L	W 14 L	16.9	58.5	26.7	178.5	700	STD
	23.1 - 30	151 A8	DW 20 B DW 20 A	-	23.6	66.9	30.4	205.4	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
9.5 - 30	111 A8	W 8	W 7	9.5	47.2	22.3	138.9	-	STD
18.4 - 30	140 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	STD
14.9 - 30	127 A8	W 13	W 11 W 12	14.9	55.7	25.9	169.9	675	STD
18.4 - 30	140 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	HD
23.1 - 30	143 A8	DW 20 B DW 20 A	-	23.6	66.9	30.4	205.4	-	STD
18.4 - 30	145 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	STD
18.4 - 30	135 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	STD
23.1 - 30	143 A8	DW 20 B DW 20 A	-	23.6	66.9	30.4	205.4	-	STD
18.4 - 30	145 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	HD
7.2 - 30	91 A8	W 6	-	7.3	43.1	20.6	126.7	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 30	140 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	HD
16.9 - 30	132 A8	W 15 L	W 14 L	16.9	58.5	26.7	178.5	700	STD
15 - 30 (18.4 - 30)	147 A8	W 16 L	W 15 L	18.1	60.8	28.1	178.8	725	STD
16.9 - 30 (14 - 30)	145 A8	W 15 L	W 14 L	16.9	58.5	26.7	178.5	700	STD
15 - 30 (18.4 - 30)	145 A8	W 16 L	W 15 L	18.1	60.8	28.1	178.8	725	STD
18.4 - 30	135 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	HD
23.1 - 30	151 A8	DW 20 B DW 20 A	-	23.6	66.9	30.4	205.4	-	DB
23.1 - 30	160 A8	DW 20 B DW 20 A	-	23.6	66.9	30.4	205.4	-	DB
Ø32"	12.4 - 32	W 11	W 9 W 10	12.8	53.5	25.2	157.4	650	STD
	12.4 - 32	W 11	W 9 W 10	12.8	53.5	25.2	157.4	650	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
12.4 - 32	124 A8	W 11	W 9 W 10	12.8	53.5	25.2	157.4	650	HD
8.3 - 32	107 A8	W 7	W 6	8.3	47.0	22.5	141.1	-	STD
8.3 - 32	101 A8	W 7	W 6	8.3	47.0	22.5	141.1	-	STD
9.5 - 32	106 A8	W 8	W 7	9.3	49.4	23.4	145.1	-	STD
12.4 - 32	115 A8	W 11	W 9 W 10	12.8	53.5	25.2	157.4	650	STD
11.2 - 32	116 A8	W 10	W 9	11.3	51.6	24.2	157.8	-	HD
16.9 - 34	142 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	HD
18.4 - 34	146 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	STD
18.4 - 34	143 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	HD
23.1 - 34	150 A8	DW 20 B DW 20 A	-	23.0	71.3	32.8	209.5	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 34	150 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	HD
18.4 - 34	150 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	STD
16.9 - 34	140 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	HD
16.9 - 34	140 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	STD
16.9 - 34	138 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	STD
18.4 - 34	137 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	STD
16.9 - 34	134 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	HD
16.9 - 34	134 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	STD
18.4 - 34	146 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	HD SPL
18.4 - 34	132 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 34	146 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	HD
23.1 - 34	150 A8	DW 20 B DW 20 A	-	23.0	71.3	32.8	209.5	-	STD
18.4 - 34	137 A8	W 16 L	W 15 L	18.4	65.0	28.8	191.3	775	HD
16.9 - 34	138 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	HD
18.4 - 34	143 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	STD
13.6 - 36	130 A8	W 12	W 11	13.6	59.6	28.1	184.5	725	STD
12.4 - 36	127 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	HD
12.4 - 36	123 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	HD
13.6 - 36	130 A8	W 12	W 11	13.6	59.6	28.1	184.5	725	HD
12.4 - 36	135 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
12.4 - 36	127 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	STD
12.4 - 36	131 A8	W 11	W 9 W 10	12.8	57.7	27.0	179.4	700	HD
9.5 - 36	118 A8	W 8	W 7	9.3	53.5	25.4	157.5	-	STD
12.4 - 36	123 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	STD
12.4 - 36	135 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	HD
8.3 - 36	104 A8	W 7	W 6	8.3	51.0	24.7	158.6	-	STD
13.6 - 36	121 A8	W 12	W 11	13.6	59.6	28.1	184.5	725	STD
8.3 - 36	109 A8	W 7	W 6	8.3	51.0	24.7	158.6	-	STD
13.6 - 36	125 A8	W 12	W 11	13.6	59.6	28.0	184.5	725	STD
12.4 - 36	131 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
NEW	12.4 - 36	135 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	STD
	11.2 - 36	126 A8	W 10	W 9	11.42	56.30			-	HD
Ø38"	13.6 - 38 (14.00 - 38)	135 A8	W 12	W 11	14.0	61.6	28.9	190.2	750	STD
	15.5 - 38	129 A8	W 14 L	-	15.6	62.4	29.4	183.5	-	STD
	15.5 - 38	134 A8	W 14 L	-	15.6	62.4	29.4	183.5	-	STD
	15.5 - 38	137 A8	W 14 L	-	15.6	62.4	29.4	183.5	-	STD
	18.4 - 38	149 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	HD
	18.4 - 38	145 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	HD
	20.8 - 38	162 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	DB HD
	15.5 - 38	129 A8	W 14 L	-	15.6	62.4	28.9	186.9	-	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
16.9 - 38	139 A8	W 15 L	W 14 L	16.9	66.3	31.0	195.0	800	STD
20.8 - 38	152 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	HD
15.5 - 38	129 A8	W 14 L	-	15.6	62.4	29.4	183.5	-	HD
11.2 - 38	113 A8	W 10	W 9	11.2	57.5	27.0	173.6	-	STD
13.6 - 38 (14.00 - 38)	127 A8	W 12	W 11	13.6	61.6	28.9	190.2	750	STD
20.8 - 38	144 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	STD
13.6 - 38 (14.00 - 38)	138 A8	W 12	W 11	13.6	61.6	28.9	190.2	750	STD
16.9 - 38	136 A8	W 15 L	W 14 L	16.9	66.3	31.0	195.0	800	HD
14.00 - 38 (13.6 - 38)	127 A8	W 12	W 11	13.6	61.6	28.9	190.2	750	STD
20.8 - 38	162 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	DB HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 38	139 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	HD
13.6 - 38 (14.00 - 38)	127 A8	W 12	W 11	13.6	61.6	28.9	190.2	750	HD
12.4 - 38	124 A8	W 11	W 9 W 10	12.8	60.0	28.3	183.9	-	STD
16.9 - 38	139 A8	W 15 L	W 14 L	16.9	66.3	31.0	195.0	800	HD
20.8 - 38	155 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	STD
15.5 - 38	134 A8	W 14 L	-	15.6	62.4	29.4	187.4	-	HD
13.6 - 38 (14.00 - 38)	135 A8	W 12	W 11	13.6	61.6	28.9	190.2	750	HD
20.8 - 38	152 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	STD
20.8 - 38	159 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	DB HD
12.4 - 38	135 A8	W 11	W 9 W 10	12.8	60.0	28.3	183.9	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index			

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
14.00 - 38 (13.6 - 38)	135 A8	W 12	W 11	13.6	61.6	28.9	190.2	750	SPL
18.4 - 38	145 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	HD
18.4 - 38	151 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	STD
18.4 - 38	149 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	STD
16.9 - 38	142 A8	W 15 L	W 14 L	16.9	66.3	31.0	195.0	800	STD
16.9 - 38	136 A8	W 15 L	W 14 L	16.9	66.3	31.0	195.0	800	STD
20.8 - 38	152 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	STD
18.4 - 38	139 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	STD
12.4 - 38	135 A8	W 11	W 9 W 10	12.8	60.0	28.3	183.9	-	STD
18.4 - 38	149 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø42"	20.8 - 42	164 A8	W 18 L	W 16 L	21.1	76.8	35.8	225.7	-	DB HD
	20.8 - 42 (42)	154 A8	W 18 L	W 16 L	21.1	76.8	35.8	225.7	-	STD
	12.4 - 42	130 A8	W 10 W 10 A	-	12.7	64.2	30.3	197.3	-	STD
	20.8 - 42	154 A8	W 18 L	W 16 L	21.1	76.8	35.8	225.7	-	STD
	20.8 - 42	161 A8	W 18 L	W 16 L	21.1	76.8	35.8	225.7	-	STD
	9.5 - 42	121 A8	W 8	W 7	9.7	59.4	28.4	183.6	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
			
Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index			

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baikrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026