


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>200/70 R 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / TRACTOR / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	94 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94026869	<b>RC (IN)</b>	81.1
<b>SW (IN)</b>	7.8	<b>RIM REC</b>	W 6
<b>OD (IN)</b>	27.0	<b>RIM ALT</b>	W 7
<b>SLR (IN)</b>	12.4	<b>ECE</b>	E4-106R-000607

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	690	800	930	1040	1160	1280	1380	1480
25	690	800	930	1040	1160	1280	1380	1480
20	750	860	990	1110	1250	1370	1480	1590
5 LT	940	1080	1230	1390	1550	1710	1850	1980
5 HT	750	860	990	1110	1250	1370	1480	1590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.