


RIDEMAX FL 693 M



| | |
|---------------------|--|
| TYRE SIZE | 560/55 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | TRAILER / IMPLEMENTS |
| VERSION | STANDARD |
| TL/TT | TL |
| LI/SS | 158 D ; 155 E |

DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|----------------|----------------|
| USA CODE | 94037353 | RC (IN) | 142.3 |
| SW (IN) | 21.4 | RIM REC | AG 16.00 |
| OD (IN) | 46.5 | RIM ALT | 17.00 ; 20.00 |
| SLR (IN) | 21.0 | ECE | E4-106R-000631 |

LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|
| 45 | 3160 | 3590 | 4280 | 5050 | 5780 | 6420 | 7180 | 7860 | 8540 |
| 40 | 3470 | 3940 | 4680 | 5530 | 6330 | 7030 | 7870 | 8620 | 9370 |
| 30 | 4210 | 4770 | 5680 | 6700 | 7660 | 8510 | 9530 | 10440 | 11340 |
| 25 | 4720 | 5360 | 6370 | 7530 | 8610 | 9560 | 10710 | 11730 | 12740 |
| 15 | 5490 | 6230 | 7410 | 8740 | 10000 | 11110 | 12440 | 13620 | 14800 |
| 5 | 6250 | 7090 | 8430 | 9950 | 11390 | 12650 | 14170 | 15520 | 16860 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.