


# AT 603

|                           |  |
|---------------------------|--|
| <b>TIRE SIZE</b>          | <b>12.5/80 -18</b>   |
| <b>UM</b>                 | IS STANDARD  |
| <b>CONSTRUCTION</b>       |  BIAS                     |
| <b>MACHINERY</b>          | MAQUINARIA AGRÍCOLA /<br>MAQUINARIA AGRÍCOLA / CARGADORA<br>RETROEXCAVADORA / CARGADORA<br>RETROEXCAVADORA |
| <b>VERSIÓN</b>            | SPECIAL  |
| <b>TIRE TYPE</b>          | TL   |
| <b>LI/SS DRIVE WHEEL</b>  | 129 A8   |
| <b>LI/SS FREE ROLLING</b> | 142 A8   |



## DIMENSIONES IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 308  | <b>RIM REC</b> | W 9            |
| <b>OD (MM)</b>  | 1000 | <b>RIM ALT</b> | 11             |
| <b>SLR (MM)</b> | 448  | <b>ECE</b>     | E4-106R-004350 |
| <b>RC (MM)</b>  | 3027 | <b>PR</b>      | 12             |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.70</b> |
|-------------------|-------------|
| <b>10 FR</b>      | 3710        |
| <b>25 FR</b>      | 3155        |
| <b>30 FR</b>      | 2970        |
| <b>40 FR</b>      | 2650        |
| <b>10 DW</b>      | 2590        |
| <b>25 DW</b>      | 2200        |
| <b>30 DW</b>      | 2070        |
| <b>40 DW</b>      | 1850        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.