

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>520/85 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ОПРЫСКИВАТЕЛЬ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	170 A8/B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	516	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1849	<b>RIM ALT</b>	DW 18 L ; DD 16 L
<b>SLR (MM)</b>	847	<b>ECE</b>	E4-106R-001411
<b>RC (MM)</b>	5595	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	2170	2650	3255	3875	4440	4740	5220	5640	6000
40	2170	2650	3255	3875	4440	4740	5220	5640	6000
30	2325	2740	3490	4150	4755	5075	5590	6035	6420
10 LT	2910	3430	4365	5195	5950	6355	6995	7560	8040
10 HT	2325	2740	3490	4150	4755	5075	5590	6035	6420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.