


# PL 801

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 7.00 - 15   |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> |  BIAS  |
| <b>MACHINERY</b>    | ROTOR RAKE/ TEDDER / HAY<br>HARVESTER / FORKLIFT / HARVESTER<br>/ IMPLEMENTS / FORKLIFT |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |



## DIMENSIONS US STANDARD

|                 |          |                |             |
|-----------------|----------|----------------|-------------|
| <b>USA CODE</b> | 94007233 | <b>RIM ALT</b> | 4.33 R; 5.0 |
| <b>SW (IN)</b>  | 7.9      | <b>PR</b>      | 12          |
| <b>OD (IN)</b>  | 29.5     |                |             |
| <b>RIM REC</b>  | 5.5      |                |             |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI          | 120  |
|--------------------|------|
| 15 LOAD WHEEL      | 6770 |
| 15 STEER WHEEL     | 5205 |
| 5 OTHER VEHICLES   | 6770 |
| 15 OTHER VEHICLES  | 5205 |
| STATIC SIDE LOADER | 7860 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.