

EARTHMAX SR 45 PLUS



EARTHMAX
RADIAL OTR TIRES

EARTHMAX SR 45 PLUS

EARTHMAX SR 45 PLUS is an All Steel radial tyre specially designed for rigid haul trucks. It is ideal for operations in long hauls. The tread pattern of the EARTHMAX SR 45 PLUS minimizes vibration and noise.



	SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
						REC RIM	ALT RIM							
														
Ø49"	27.00 R 49	TL	E4	**	223 B	19.50/4.0	--	540	746	2702	1214	8095	73	STD
	27.00 R 49	TL	E4	**	223 B	19.50/4.0	--	654	746	2702	1214	8095	73	HRC
	27.00 R 49	TL	E4	**	223 B	19.50/4.0	--	440	746	2702	1214	8095	73	CR
Ø51"	33.00 R 51	TL	E4	**	235 B	24.00/5.0	-	705	910	3065	1369	9313	90	STD

STD: STANDARD, HRC: HEAT RESISTANT COMPOUND, CR: CUT RESISTANT COMPOUND

TECHNOLOGIES					PERFORMANCES			
								
								
B	235 kg							

Permissible tolerances: O.D. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. BKT reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026

SIZE	TT/TL	TRA CODE	STAR RATING	LI/SS	RIM		TKPH (TK/H)	OW (MM) (mm)	OD (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (MM)	VERSION
					REC RIM	ALT RIM							
													
33.00 R 51	TL	E4	**	235 B	24.00/5.0	-	815	910	3065	1369	9313	90	HRC
33.00 R 51	TL	E4	**	235 B	24.00/5.0	-	605	910	3065	1369	9313	90	CR

STD: STANDARD, HRC: HEAT RESISTANT COMPOUND, CR: CUT RESISTANT COMPOUND



TECHNOLOGIES				PERFORMANCES			
							
E4							
B							
235 kg							

Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balakrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

GB – 23/09/2026