

# BK 826

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>8.25 - 16</b>  |
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | ⊠ BIAS  |
| <b>MACHINERY</b>    | RIMORCHIO / ATTREZZI AGRICOLI /<br>MIETITREBBIA / RIMORCHIO / TERNA |
| <b>VERSIONE</b>     | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |



## DIMENSIONI US STANDARD

|                   |          |                |        |
|-------------------|----------|----------------|--------|
| <b>CODICE USA</b> | 94013289 | <b>RIM ALT</b> | 6.00 G |
| <b>SW (IN)</b>    | 9.4      | <b>PR</b>      | 8      |
| <b>OD (IN)</b>    | 34.0     |                |        |
| <b>RIM REC</b>    | 6.50 H   |                |        |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>61</b> |
| <b>62 LS</b>     | 2975      |
| <b>62 LD</b>     | 2810      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.