

AGRIMAX V- FLECTO

VF 600/60 R 30

| | |
|--------------|--|
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| | 158 D |



UNDEFINED US STANDARD

| | | | |
|----------|----------|---------|------------------|
| USA CODE | 94053360 | RC (IN) | 173.4 |
| SW (IN) | 23.4 | RIM REC | DW 20 B |
| OD (IN) | 58.5 | RIM ALT | DW 18 L; DW 21 B |
| SLR (IN) | 25.6 | ECE | E11-106R-002979 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 |
|-------------------------------|------|------|------|-------|-------|-------|
| 45 | 4670 | 5460 | 6220 | 6990 | 7750 | 8520 |
| FROM 40 TO 25 | 5150 | 6000 | 6830 | 7680 | 8520 | 9370 |
| 20 | 5250 | 6110 | 6970 | 7830 | 8690 | 9560 |
| 12 | 5350 | 6230 | 7100 | 7980 | 8850 | 9740 |
| 5 | 5650 | 6590 | 7520 | 8440 | 9370 | 10310 |
| *UPTO 5 CYC WITH FRONT LOADER | 7210 | 8390 | 9570 | 10750 | 11930 | 13120 |
| 5 HT | 5250 | 6110 | 6970 | 7830 | 8690 | 9560 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.