

# RIB 774 (A)

<b>TIRE SIZE</b>	200/60 - 14.5
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS FREE ROLLING</b>	106 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94010974	<b>RC (IN)</b>	74.3
<b>SW (IN)</b>	8.3	<b>RIM REC</b>	AG 6.75
<b>OD (IN)</b>	24.0	<b>ECE</b>	E4-106R-002664
<b>SLR (IN)</b>	11.3	<b>PR</b>	10

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>73</b>
5 FR	2930
15 FR	2490
20 FR	2350
25 FR	2090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.