


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>340/85 R 28</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	139 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	353	<b>RIM REC</b>	W 12
<b>OD (MM)</b>	1315	<b>RIM ALT</b>	W 11
<b>SLR (MM)</b>	603	<b>ECE</b>	E11-106R-008233
<b>RC (MM)</b>	3963	<b>SRI</b>	625

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
<b>50</b>	950	1120	1290	1435	1605	1750	1920	2070	2260	2430
<b>40</b>	950	1120	1280	1435	1605	1750	1920	2070	2260	2430
<b>30</b>	1020	1200	1385	1540	1720	1880	2060	2215	2425	2605
<b>10 LT</b>	1275	1500	1730	1925	2155	2350	2580	2775	3035	3260
<b>10 HT</b>	1020	1200	1385	1540	1720	1880	2060	2215	2425	3490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.