

FLOTATION 648

TIRE SIZE	800/45 - 26.5
UM	US STANDARD
CONSTRUCTION	BIAS
MACHINERY	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	164 A8/160 B
LI/SS FREE ROLLING	177 A8/173 B



DIMENSIONER US STANDARD

USA CODE	94006564	RC (IN)	164.8
SW (IN)	31.5	RIM REC	AG 28.00
OD (IN)	54.8	ECE	E4-106R-002280
SLR (IN)	24.8	PR	16

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	26	29	32
5 FR	20030	21310	22530
10 FR	18020	19180	20280
20 FR	16030	17050	18020
25 FR	14310	15220	16090
30 FR	12870	13700	14330
5 DW	13720	14590	15430
10 DW	12350	13140	13890
20 DW	10980	11680	12350
25 DW	9800	10430	11020
30 DW	8820	9380	9920

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.