

AGRIMAX TURF RT 333

| | |
|---------------------|--|
| TIRE SIZE | 280/70 R 16 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | VENDIMIADORA / MAQUINA PARA LA RECOGIDA DE FRUTA / MINITRACTOR / TRACTOR / COSECHADORA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 112 A8 ; 112 B |



DIMENSIONES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 289 | RIM REC | W9 |
| OD (MM) | 800 | RIM ALT | W 8; W 10 |
| SLR (MM) | 359 | ECE | E11-106R-006472 |
| RC (MM) | 2371 | SRI | 380 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|-----|-----|-----|------|------|------|------|------|
| 50 | 530 | 605 | 695 | 785 | 875 | 965 | 1055 | 1120 |
| 40 | 530 | 605 | 695 | 785 | 875 | 965 | 1055 | 1120 |
| 30 | 565 | 650 | 745 | 840 | 940 | 1035 | 1130 | 1200 |
| 10 LT | 710 | 815 | 935 | 1055 | 1175 | 1295 | 1415 | 1505 |
| 10 HT | 565 | 650 | 745 | 840 | 940 | 1035 | 1130 | 1200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.