

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 480/70 R 34 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 149 D |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94062225 | RC (IN) | 187.9 |
| SW (IN) | 18.9 | RIM REC | W 15 L |
| OD (IN) | 62.2 | RIM ALT | W 14 L; W 16 L |
| SLR (IN) | 28.0 | ECE | E11-106R-005524 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-----------|------|------|------|------|------|------|------|------|
| 40 | 3370 | 3870 | 4440 | 5020 | 5590 | 6160 | 6730 | 7160 |
| 30 | 3550 | 4070 | 4670 | 5280 | 5870 | 6480 | 7090 | 7530 |
| 25 | 3690 | 4240 | 4870 | 5500 | 6130 | 6760 | 7390 | 7850 |
| 20 | 3880 | 4450 | 5110 | 5780 | 6440 | 7100 | 7760 | 8240 |
| 5 LT | 4520 | 5190 | 5960 | 6720 | 7500 | 8270 | 9030 | 9600 |
| 5 HT | 3880 | 4450 | 5110 | 5780 | 6440 | 7100 | 7760 | 7240 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.