


FL 630 SUPER

| | |
|---------------------|--|
| TIRE SIZE | 560/60 R 22.5 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ESPARCIDOR / CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 165 D |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|-----------------|
| CÓDIGO USA | 94059539 | RC (IN) | 149.0 |
| SW (IN) | 21.4 | RIM REC | AG 16.00 |
| OD (IN) | 49.0 | RIM ALT | 17.00; 20.00 |
| SLR (IN) | 21.6 | ECE | E11-106R-006945 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 73 |
|-----------|------|------|------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 3430 | 3850 | 4780 | 5430 | 6280 | 7120 | 7780 | 8530 | 9370 | 10470 |
| 40 | 3730 | 4190 | 5200 | 5920 | 6830 | 7750 | 8470 | 9280 | 10200 | 11350 |
| 30 | 4520 | 5070 | 6300 | 7160 | 8280 | 9390 | 10250 | 11240 | 12350 | 13750 |
| 25 | 5070 | 5690 | 7080 | 8050 | 9290 | 10550 | 11520 | 12620 | 13870 | 15440 |
| 15 | 5890 | 6610 | 8220 | 9350 | 10800 | 12260 | 13380 | 14670 | 16110 | 17940 |
| 5 | 6700 | 7530 | 9370 | 10650 | 12300 | 13950 | 15230 | 16710 | 18350 | 20440 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.