DATA SHEET

Última actualizac
2-06-2026

AGRIMAX TURF RT 333

TIRE SIZE	**215/65 R 14**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	VENDIMIADORA / MAQUINA PARA LA RECOGIDA DE FRUTA / MINITRACTOR / TRACTOR / COSECHADORA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	90 A8 ; 90 B

DIMENSIONES US STANDARD

CÓDIGO USA	94076277	**RC (IN)**	75.0
SW (IN)	8.7	**RIM REC**	W 7
OD (IN)	24.8	**RIM ALT**	W 6
SLR (IN)	11.4	**ECE**	E11-106R-0010331

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29
30	620	720	830	920	1030	1130	1330
25	620	720	830	920	1030	1130	1330
20	670	780	890	1000	1110	1220	1430
5 LT	830	960	1110	1240	1370	1520	1780
5 HT	670	780	890	1000	1110	1220	1430

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..