

# AGRIMAX RT 657

|                  |                                          |
|------------------|------------------------------------------|
| <b>TIRE SIZE</b> | <b>540/65 R 28</b>                       |
| <b>UM</b>        | IS STANDARD                              |
| <b>MACHINERY</b> | VINEYARD HARVESTER / TRACTOR / HARVESTER |
| <b>VERSION</b>   | SPECIAL                                  |
| <b>TL/TT</b>     | TL                                       |
| <b>LI/SS</b>     | 149 D ; 152 A8                           |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 530  | <b>RIM REC</b> | W 16 L         |
| <b>OD (MM)</b>  | 1413 | <b>RIM ALT</b> | W 18 L         |
| <b>SLR (MM)</b> | 643  | <b>ECE</b>     | E4-106R-000650 |
| <b>RC (MM)</b>  | 4253 | <b>SRI</b>     | 675            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR   | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|--------------|------|------|------|------|------|------|------|------|
| <b>65</b>    | 1560 | 1820 | 2050 | 2275 | 2505 | 2700 | 2990 | 3250 |
| <b>50</b>    | 1640 | 1915 | 2155 | 2395 | 2630 | 2835 | 3145 | 3415 |
| <b>40</b>    | 1705 | 1990 | 2240 | 2485 | 2735 | 2950 | 3270 | 3550 |
| <b>30</b>    | 1800 | 2095 | 2360 | 2620 | 2880 | 3105 | 3445 | 3740 |
| <b>10 LT</b> | 2095 | 2440 | 2745 | 3050 | 3355 | 3615 | 4010 | 4355 |
| <b>10 HT</b> | 1800 | 2095 | 2360 | 2620 | 2880 | 3105 | 3445 | 3740 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.