

# AT 621

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 12.5 - 20   |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> |   |
| <b>MACHINERY</b>    | COMPACT LOADER / BACKHOE<br>LOADER / BACKHOE LOADER /<br>LOADER |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |



## DIMENSIONS IS STANDARD

|                 |      |                 |                 |
|-----------------|------|-----------------|-----------------|
| <b>SW (MM)</b>  | 325  | <b>RIM REC</b>  | 11.0            |
| <b>OD (MM)</b>  | 1040 | <b>ECE</b>      | E11-106R-005293 |
| <b>SLR (MM)</b> | 480  | <b>PR</b>       | 12              |
| <b>RC (MM)</b>  | 3103 | <b>TRA CODE</b> | R4              |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.50</b> |
| <b>40 FR</b>      | 3350        |
| <b>40 DW</b>      | 2300        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.