DATA SHEET

PRINTED ON

MULTIMAX MP 525

TIRE SIZE	**405/70 R 18**
UM	US STANDARD
CONSTRUCTION	RADIAL
MACHINERY	VEHÍCULO UNIVERSAL / ELEVADOR TELESCÓPICO / CARGADORA COMPACTA / ELEVADOR TELESCÓPICO / MOTONIVELADORA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	146 J ; 141 B ; 153 A2

DIMENSIONES US STANDARD

CÓDIGO USA	94075539	**RIM REC**	13
OD (IN)	40.4	**RIM ALT**	11; 12
SLR (IN)	18.2	**ECE**	E11-54R-0022030
RC (IN)	122.9		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	54	58
62	6150	6600
30	5680	-
5	8050	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..