


# MULTIMAX MP 527

<b>TIRE SIZE</b>	<b>400/80 R 24 IND</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE / CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	162 A8/B



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94052226	<b>RC (IN)</b>	150.9
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	DW 13
<b>OD (IN)</b>	49.2	<b>RIM ALT</b>	DW 12 ; DW 13 L ; DW 14 L
<b>SLR (IN)</b>	22.8	<b>ECE</b>	E11-106R-002982

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	49	52	58	64	67	70	73	75	78
<b>30</b>	4090	4820	5650	6390	7120	7390	7760	8590	9300	9780	10010	10470	-	-
<b>25</b>	4090	4820	5650	6390	7120	7390	7760	8590	9300	9780	10010	10470	-	-
<b>20</b>	4380	5160	6060	6840	7630	7910	8310	9190	9950	10460	10710	11210	-	-
<b>15</b>	4540	5360	6280	7100	7910	8210	8620	9550	10340	10860	11110	11630	-	-
<b>5 CYC.</b>	5030	6140	7230	8490	9590	10140	10680	11640	12890	13430	13950	14670	15010	15710
<b>STATIC</b>	7720	9410	11090	13010	14700	15540	16380	17860	19750	20590	21410	22500	23030	24080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.