

TR 135



TR 135



TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning proprieties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.



	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø16"	12.4 - 16	93 A8	W 11	W 9 9 W 10	12.8	37.8	17.0	112.3	-	STD
	12.4 - 16	107 A8	W 11	W 9 9 W 10	12.8	37.8	17.0	112.3	-	STD
Ø20"	9.5 - 20	104 A8	W 8	W 7	9.4	37.6	17.9	113.7	-	HD
	8.00 - 20	107 A8	5.50 F	-	8.9	38.0	17.6	111.7	-	STD
	12.4 - 20	112 A8	W 11	W 9 9 W 10 11	12.8	42.3	19.7	124.4	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
11.2 - 20	107 A8	W 10	W 9 9	11.5	40.2	18.3	121.1	-	STD
10.00 - 20	152 A2	7.5	-	11.0	42.3	19.5	124.4	-	STD
9.5 - 20	104 A8	W 8	W 7	9.4	37.6	17.9	113.7	-	STD
8.00 - 20	101 A8	5.50 F	-	8.9	38.0	17.6	111.7	-	STD
9.5 - 20	99 A8	W 8	W 7	9.4	37.6	17.5	113.4	-	STD
12.4 - 20	112 A8	W 11	W 9 9 W 10 11	12.8	42.3	19.7	124.4	-	HD
Ø24"	12.4 - 24	124 A8	W 11 W 9 W 10	12.4	45.7	21.4	140.7	550	STD
	13.6 - 24	120 A8	W 12 W 11	14.0	48.0	22.1	145.6	-	STD
	8.3 - 24	96 A8	W 7 W 6	8.3	39.2	18.5	117.5	-	STD
	13.6 - 24	120 A8	W 12 W 11	14.0	48.0	22.1	145.6	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
12.4 - 24	118 A8	W 11	W 9 W 10	12.4	45.7	20.9	136.9	550	HD
11.2 - 24	113 A8	W 10	W 9	11.2	43.5	20.0	130.0	525	HD
14.9 - 24	132 A8	W 13	W 12 W 11	14.9	49.8	22.7	151.1	600	STD
12.4 - 24	122 A8	W 11	W 9 W 10	12.4	45.7	21.4	140.7	550	STD
8.3 - 24	101 A8	W 7	W 6	8.3	39.2	18.5	117.5	-	HD
11.2 - 24	116 A8	W 10	W 9	11.2	43.5	20.4	133.8	525	HD
13.6 - 24	126 A8	W 12	W 11	14.0	48.0	22.1	145.6	-	HD
16.9 - 24	132 A8	W 15 L	W 14 L	16.9	52.6	24.1	154.5	-	STD
14.9 - 24	132 A8	W 13	W 12 W 11	14.9	49.8	22.7	151.1	600	STD
12.4 - 24	118 A8	W 11	W 9 W 10	12.4	45.7	21.4	140.7	550	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
14.9 - 24	128 A8	W 13	W 11 W 12	14.9	49.8	22.7	151.1	600	HD
11.2 - 24	106 A8	W 10	W 9	11.2	43.5	20.4	133.8	525	STD
16.9 - 24	136 A8	W 15 L	W 14 L	16.9	52.6	23.66	160.43	-	HD
11.2 - 24	116 A8	W 10	W 9	11.2	43.5	20.4	133.8	525	HD
9.5 - 24	112 A8	W 8	W 7	9.5	41.7	19.8	127.3	-	STD
14.9 - 24	124 A8	W 13	W 12 W 11	14.9	49.8	22.7	151.1	600	STD
14.9 - 24	124 A8	W 13	W 12 W 11	14.9	49.8	22.4	148.4	600	HD
8.3 - 24	101 A8	W 7	W 6	8.3	39.2	18.7	121.1	-	STD
16.9 - 24	129 A8	W 15 L	W 14 L	16.9	52.6	24.1	154.5	-	HD
14.9 - 24	132 A8	W 13	W 12 W 11	14.9	49.8	22.7	151.1	600	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
11.2 - 24	113 A8	W 10	W 9	11.2	43.5	20.4	133.8	25	STD
12.4 - 24	124 A8	W 11	W 9 W 10	12.4	45.7	21.4	140.7	550	SPL
14.9 - 24	124 A8	W 13	W 12 W 11	14.9	49.8	22.7	151.1	600	STD
14.9 - 24	124 A8	W 13	W 11 W 12	14.9	49.8	22.4	148.4	600	HD
11.2 - 24	113 A8	W 10	W 9	11.2	43.5	20.4	133.8	525	STD
13.6 - 24	120 A8	W 12	W 11	14.0	48.0	22.1	145.6	-	HD
12.4 - 24	118 A8	W 11	W 9 W 10	12.4	45.7	21.4	138.7	550	STD
16.9 - 24	129 A8	W 15 L	W 14 L	16.9	52.6	24.1	154.5	-	STD
9.5 - 24	112 A8	W 8	W 7	9.5	41.7	19.8	127.3	-	HD
13.6 - 24	126 A8	W 12	W 11	14.0	48.0	22.1	145.6	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
16.9 - 24	132 A8	W 15 L	W 14 L	16.9	52.6	24.1	154.5	-	STD
9.5 - 24	108 A8	W 8	W 7	9.5	41.7	19.8	127.3	-	HD
9.5 - 24	108 A8	W 8	W 7	9.5	41.7	19.8	127.3	-	STD
8.3 - 24	107 A8	W 7	W 6	8.3	39.2	18.5	117.5	-	HD
16.9 - 24	129 A8	W 15 L	W 14 L	16.9	52.6	24.1	154.5	-	STD
12.4 - 24	111 A8	W 11	W 9 W 10	12.4	45.7	21.4	140.7	550	STD
12.4 - 24	118 A8	W 11	W 9 W 10	12.4	45.7	20.9	136.9	550	HD
9.5 - 24	102 A8	W 8	W 7	9.5	41.7	19.8	127.3	-	STD
12.4 - 24	124 A8	W 11	W 9 W 10	12.4	45.7	21.4	140.7	550	STD
Ø26"	14.9 - 26	125 A8	W 13 W 11 W 12	14.8	51.8	23.6	155.4	-	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
23.1 - 26	149 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	STD
23.1 - 26	157 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	DB
23.1 - 26	155 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	DB
23.1 - 26	149 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	STD
16.9 - 26	133 A8	W 15 L	W 14 L	16.9	54.3	24.6	164.7	-	STD
23.1 - 26	149 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	DB
16.9 - 26	136 A8	W 15 L	W 14 L	16.9	54.3	24.6	164.7	-	STD
23.1 - 26	155 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	STD
16.9 - 26	133 A8	W 15 L	W 14 L	16.9	54.3	24.6	164.7	-	STD
23.1 - 26	155 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
R1	164 lbs		

Permissible tolerances: O.O. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
23.1 - 26	155 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	STD
14.9 - 26	132 A8	W 13	W 11 W 12	14.8	51.8	23.6	155.4	-	STD
23.1 - 26	152 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	STD
14.9 - 26	125 A8	W 13	W 11 W 12	14.8	51.8	23.6	155.4	-	STD
23.1 - 26	155 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	DB HD
23.1 - 26	149 A8	DW 20 B DW 20 A	-	23.1	62.4	27.6	181.7	750	DB
Ø28"	14.9 - 28	121 A8	W 13 W 11 W 12	14.9	53.7	25.0	164.2	650	STD
	11.2 - 28	114 A8	W 10 W 9	11.2	47.4	22.2	139.5	575	STD
	9.5 - 28	104 A8	W 8 W 7	9.3	45.5	21.6	140.0	-	STD
	13.6 - 28	130 A8	W 12 W 11	13.6	51.6	23.9	153.9	625	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
8.3 - 28	104 A8	W 7	W 6	8.4	43.5	20.4	131.8	-	STD
14.9 - 28	133 A8	W 13	W 11 W 12	14.9	53.7	25.0	164.2	650	STD
18.4 - 28	144 A8	W 16 L	W 15 L	18.4	59.1	27.2	173.7	-	STD
14.9 - 28	135 A8	W 13	W 11 W 12	14.9	53.7	25.0	164.2	650	STD
12.4 - 28	127 A8	W 11	W 9 W 10	12.8	49.6	23.0	152.6	600	STD
14.9 - 28 (28)	126 A8	W 13	W 11 W 12	14.9	53.7	25.0	164.2	650	STD
12.4 - 28	120 A8	W 11	W 9 W 10	12.8	49.6	23.0	152.6	600	HD
14.9 - 28	133 A8	W 13	W 11 W 12	14.9	53.7	25.0	164.2	650	HD
11.2 - 28	119 A8	W 10	W 9	11.2	47.4	22.2	139.5	575	STD
9.5 - 28	110 A8	W 8	W 7	9.3	45.5	21.6	140.0	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
13.6 - 28	133 A8	W 12	W 11	13.6	51.6	23.9	153.9	625	STD
14.9 - 28	126 A8	W 13	W 11 W 12	14.9	53.7	25.0	164.2	650	HD
8.3 - 28	99 A8	W 7	W 6	8.4	43.5	20.4	131.8	-	STD
14.9 - 28	126 A8	W 13	W 11 W 12	14.9	53.7	25.0	164.2	650	STD
13.6 - 28	122 A8	W 12	W 11	13.6	51.6	23.9	153.9	625	STD
13.6 - 28	122 A8	W 12	W 11	13.6	51.6	23.9	158.4	625	HD
12.4 - 28	120 A8	W 11	W 9 W 10	12.8	49.6	23.0	152.6	600	STD
12.4 - 28	113 A8	W 11	W 9 W 10	12.8	49.6	23.0	152.6	600	STD
12.4 - 28	123 A8	W 11	W 9 W 10	12.8	49.6	23.0	152.6	600	STD
11.2 - 28	114 A8	W 10	W 9	11.2	47.4	22.2	139.5	575	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
	18.4 - 28	134 A8	W 16 L	W 15 L	18.4	59.1	27.2	173.7	-	STD
Ø30"	18.4 - 30	145 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	STD
	23.1 - 30	160 A8	DW 20 B DW 20 A	-	23.6	66.9	30.4	205.4	-	DB
	18.4 - 30	150 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	STD
	18.4 - 30	147 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	STD
	9.5 - 30	105 A8	W 8	W 7	9.5	47.2	22.3	138.9	-	STD
	16.9 - 30	136 A8	W 15 L	W 14 L	16.9	58.5	26.7	178.5	700	STD
	23.1 - 30	151 A8	DW 20 B DW 20 A	-	23.6	66.9	31.4	198.7	-	STD
	16.9 - 30 (14 - 30)	143 A8	W 15 L	W 14 L	16.9	58.5	26.7	178.5	700	STD
	23.1 - 30	151 A8	DW 20 B DW 20 A	-	23.6	66.9	30.4	205.4	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
9.5 - 30	111 A8	W 8	W 7	9.5	47.2	22.3	138.9	-	STD
18.4 - 30	140 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	STD
14.9 - 30	127 A8	W 13	W 11 W 12	14.9	55.7	25.9	169.9	675	STD
18.4 - 30	140 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	HD
23.1 - 30	143 A8	DW 20 B DW 20 A	-	23.6	66.9	30.4	205.4	-	STD
18.4 - 30	145 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	STD
18.4 - 30	135 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	STD
23.1 - 30	143 A8	DW 20 B DW 20 A	-	23.6	66.9	30.4	205.4	-	STD
18.4 - 30	145 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	HD
7.2 - 30	91 A8	W 6	-	7.3	43.1	20.6	126.7	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 30	140 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	HD
16.9 - 30	132 A8	W 15 L	W 14 L	16.9	58.5	26.7	178.5	700	STD
15 - 30 (18.4 - 30)	147 A8	W 16 L	W 15 L	18.1	60.8	28.1	178.8	725	STD
16.9 - 30 (14 - 30)	145 A8	W 15 L	W 14 L	16.9	58.5	26.7	178.5	700	STD
15 - 30 (18.4 - 30)	145 A8	W 16 L	W 15 L	18.1	60.8	28.1	178.8	725	STD
18.4 - 30	135 A8	W 16 L	W 15 L	18.1	60.8	27.4	185.5	725	HD
23.1 - 30	151 A8	DW 20 B DW 20 A	-	23.6	66.9	30.4	205.4	-	DB
23.1 - 30	160 A8	DW 20 B DW 20 A	-	23.6	66.9	30.4	205.4	-	DB
Ø32"	12.4 - 32	121 A8	W 11 W 9 W 10	12.8	53.5	25.2	157.4	650	STD
	12.4 - 32	121 A8	W 11 W 9 W 10	12.8	53.5	25.2	157.4	650	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
12.4 - 32	124 A8	W 11	W 9 W 10	12.8	53.5	25.2	157.4	650	HD
8.3 - 32	107 A8	W 7	W 6	8.3	47.0	22.5	141.1	-	STD
8.3 - 32	101 A8	W 7	W 6	8.3	47.0	22.5	141.1	-	STD
9.5 - 32	106 A8	W 8	W 7	9.3	49.4	23.4	145.1	-	STD
12.4 - 32	115 A8	W 11	W 9 W 10	12.8	53.5	25.2	157.4	650	STD
11.2 - 32	116 A8	W 10	W 9	11.3	51.6	24.2	157.8	-	HD
16.9 - 34	142 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	HD
18.4 - 34	146 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	STD
18.4 - 34	143 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	HD
23.1 - 34	150 A8	DW 20 B DW 20 A	-	23.0	71.3	32.8	209.5	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index			

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 34	150 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	HD
18.4 - 34	150 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	STD
16.9 - 34	140 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	HD
16.9 - 34	140 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	STD
16.9 - 34	138 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	STD
18.4 - 34	137 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	STD
16.9 - 34	134 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	HD
16.9 - 34	134 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	STD
18.4 - 34	146 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	HD SPL
18.4 - 34	132 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
			
R1		A8	
164 lbs		164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 34	146 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	HD
23.1 - 34	150 A8	DW 20 B DW 20 A	-	23.0	71.3	32.8	209.5	-	STD
18.4 - 34	137 A8	W 16 L	W 15 L	18.4	65.0	28.8	191.3	775	HD
16.9 - 34	138 A8	W 15 L	W 14 L	16.9	62.4	28.7	188.7	750	HD
18.4 - 34	143 A8	W 16 L	W 15 L	18.4	65.0	29.6	197.2	775	STD
13.6 - 36	130 A8	W 12	W 11	13.6	59.6	28.1	184.5	725	STD
12.4 - 36	127 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	HD
12.4 - 36	123 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	HD
13.6 - 36	130 A8	W 12	W 11	13.6	59.6	28.1	184.5	725	HD
12.4 - 36	135 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
12.4 - 36	127 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	STD
12.4 - 36	131 A8	W 11	W 9 W 10	12.8	57.7	27.0	179.4	700	HD
9.5 - 36	118 A8	W 8	W 7	9.3	53.5	25.4	157.5	-	STD
12.4 - 36	123 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	STD
12.4 - 36	135 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	HD
8.3 - 36	104 A8	W 7	W 6	8.3	51.0	24.7	158.6	-	STD
13.6 - 36	121 A8	W 12	W 11	13.6	59.6	28.1	184.5	725	STD
8.3 - 36	109 A8	W 7	W 6	8.3	51.0	24.7	158.6	-	STD
13.6 - 36	125 A8	W 12	W 11	13.6	59.6	28.0	184.5	725	STD
12.4 - 36	131 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
NEW	12.4 - 36	135 A8	W 11	W 9 W 10	12.8	57.7	27.4	179.0	700	STD
	11.2 - 36	126 A8	W 10	W 9	11.42	56.30			-	HD
Ø38"	13.6 - 38 (14.00 - 38)	135 A8	W 12	W 11	14.0	61.6	28.9	190.2	750	STD
	15.5 - 38	129 A8	W 14 L	-	15.6	62.4	29.4	183.5	-	STD
	15.5 - 38	134 A8	W 14 L	-	15.6	62.4	29.4	183.5	-	STD
	15.5 - 38	137 A8	W 14 L	-	15.6	62.4	29.4	183.5	-	STD
	18.4 - 38	149 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	HD
	18.4 - 38	145 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	HD
	20.8 - 38	162 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	DB HD
	15.5 - 38	129 A8	W 14 L	-	15.6	62.4	28.9	186.9	-	HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
16.9 - 38	139 A8	W 15 L	W 14 L	16.9	66.3	31.0	195.0	800	STD
20.8 - 38	152 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	HD
15.5 - 38	129 A8	W 14 L	-	15.6	62.4	29.4	183.5	-	HD
11.2 - 38	113 A8	W 10	W 9	11.2	57.5	27.0	173.6	-	STD
13.6 - 38 (14.00 - 38)	127 A8	W 12	W 11	13.6	61.6	28.9	190.2	750	STD
20.8 - 38	144 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	STD
13.6 - 38 (14.00 - 38)	138 A8	W 12	W 11	13.6	61.6	28.9	190.2	750	STD
16.9 - 38	136 A8	W 15 L	W 14 L	16.9	66.3	31.0	195.0	800	HD
14.00 - 38 (13.6 - 38)	127 A8	W 12	W 11	13.6	61.6	28.9	190.2	750	STD
20.8 - 38	162 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	DB HD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
18.4 - 38	139 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	HD
13.6 - 38 (14.00 - 38)	127 A8	W 12	W 11	13.6	61.6	28.9	190.2	750	HD
12.4 - 38	124 A8	W 11	W 9 W 10	12.8	60.0	28.3	183.9	-	STD
16.9 - 38	139 A8	W 15 L	W 14 L	16.9	66.3	31.0	195.0	800	HD
20.8 - 38	155 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	STD
15.5 - 38	134 A8	W 14 L	-	15.6	62.4	29.4	187.4	-	HD
13.6 - 38 (14.00 - 38)	135 A8	W 12	W 11	13.6	61.6	28.9	190.2	750	HD
20.8 - 38	152 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	STD
20.8 - 38	159 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	DB HD
12.4 - 38	135 A8	W 11	W 9 W 10	12.8	60.0	28.3	183.9	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
		REC RIM	ALT RIM						
									
14.00 - 38 (13.6 - 38)	135 A8	W 12	W 11	13.6	61.6	28.9	190.2	750	SPL
18.4 - 38	145 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	HD
18.4 - 38	151 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	STD
18.4 - 38	149 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	STD
16.9 - 38	142 A8	W 15 L	W 14 L	16.9	66.3	31.0	195.0	800	STD
16.9 - 38	136 A8	W 15 L	W 14 L	16.9	66.3	31.0	195.0	800	STD
20.8 - 38	152 A8	W 18 L	W 16 L	20.9	72.2	33.3	223.8	875	STD
18.4 - 38	139 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	STD
12.4 - 38	135 A8	W 11	W 9 W 10	12.8	60.0	28.3	183.9	-	STD
18.4 - 38	149 A8	W 16 L	W 15 L	18.4	68.9	31.3	211.3	825	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
			
R1	A8	164 lbs	

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (in)	OD (in)	SLR (in)	RC (in)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø42"	20.8 - 42	164 A8	W 18 L	W 16 L	21.1	76.8	35.8	225.7	-	DB HD
	20.8 - 42 (42)	154 A8	W 18 L	W 16 L	21.1	76.8	35.8	225.7	-	STD
	12.4 - 42	130 A8	W 10 W 10 A	-	12.7	64.2	30.3	197.3	-	STD
	20.8 - 42	154 A8	W 18 L	W 16 L	21.1	76.8	35.8	225.7	-	STD
	20.8 - 42	161 A8	W 18 L	W 16 L	21.1	76.8	35.8	225.7	-	STD
	9.5 - 42	121 A8	W 8	W 7	9.7	59.4	28.4	183.6	-	STD

STD: STANDARD, HD: HEAVY DUTY, DB: DUAL BEAD, DB HD: DUAL BEAD HD, HD SPL: HD SPECIAL, SPL: SPECIAL

TECHNOLOGIES		PERFORMANCES	
 R1  A8	 164 lbs		Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index
			