

FLOTATION 648

TIRE SIZE	700/50 - 22.5
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	HEUPRESSE / ERNTEMASCHINE / STREUMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	156 A8/153 B
LI/SS FREE ROLLING	168 A8/164 B



ABMESSUNGEN US STANDARD

USA-CODE	94006496	RC (IN)	148.6
SW (IN)	27.6	RIM REC	24.00
OD (IN)	50.0	ECE	E4-106R-002270
SLR (IN)	21.7	PR	12

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	23	26
5 FR	15540	16130	17280
10 FR	13990	14520	15550
20 FR	12430	12900	13820
25 FR	11100	11520	12350
30 FR	9990	10370	11020
5 DW	11100	11530	12350
10 DW	9990	10370	11110
20 DW	8870	9230	9880
25 DW	7930	8230	8820
30 DW	7130	7410	8050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.