


# AGRIMAX TERIS

<b>TIRE SIZE</b>	<b>710/55 R 28 CHO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MOISSONNEUSE / MACHINE À RÉCOLTER LE COTON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	164 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	716	<b>RIM REC</b>	DW 23 B
<b>OD (MM)</b>	1493	<b>ECE</b>	E11-106R-005940
<b>SLR (MM)</b>	663	<b>SRI</b>	700
<b>RC (MM)</b>	4442		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	1950	2250	2550	2900	3200	3550	3950	4250	4650	5000
40	1950	2250	2550	2900	3200	3550	3950	4250	4650	5000
30	2090	2410	2730	3105	3425	3800	4230	4550	4980	5350
15 CYC	3220	3715	4210	4785	5280	5860	6520	7015	7675	8250
10 CYC	3510	4050	4590	5220	5760	6390	7110	7650	8370	9000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.