


# AGRIMAX RT 955

<b>TIRE SIZE</b>	<b>230/95 R 40</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	132 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94055210	<b>RC (IN)</b>	175.0
<b>SW (IN)</b>	9.0	<b>RIM REC</b>	W 7
<b>OD (IN)</b>	57.2	<b>RIM ALT</b>	W 8
<b>SLR (IN)</b>	27.2	<b>ECE</b>	E11-106R-004066

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	17	23	29	35	41	46	52	58	64
30	1810	2340	2820	3130	3310	3620	3920	4190	4410	-
25	1810	2340	2820	3130	3310	3620	3920	4190	4410	-
20	1940	2500	3020	3350	3540	3870	4200	4490	4720	-
5	2050	2580	3170	3770	4360	4500	5030	5560	6080	6610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.