

# LOADER PLUS

|                     |                                                                                        |
|---------------------|----------------------------------------------------------------------------------------|
| <b>TIRE SIZE</b>    | <b>23.5 - 25</b>                                                                       |
| <b>UM</b>           | IS STANDARD                                                                            |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | CARREGADORA / TRATOR DE ESTEIRA<br>/ CARREGADORA / TRATOR DE<br>ESTEIRA                |
| <b>VERSÃO</b>       | STANDARD                                                                               |
| <b>TIRE TYPE</b>    | TL                                                                                     |



## DIMENSÕES IS STANDARD

|                 |           |                 |    |
|-----------------|-----------|-----------------|----|
| <b>OD (MM)</b>  | 1640      | <b>PR</b>       | 16 |
| <b>SLR (MM)</b> | 749       | <b>TRA CODE</b> | L3 |
| <b>RC (MM)</b>  | 4855      |                 |    |
| <b>RIM REC</b>  | 19.50/2.5 |                 |    |

## LOAD CAPACITY (KG/TIRE)

| <b>KM/H / BAR</b> | <b>3.00</b> |
|-------------------|-------------|
| 10                | 9500        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.