


# MULTIMAX MP 522

<b>TIRE SIZE</b>	<b>480/80 R 26</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE / CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	160 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	DW 15 L
<b>OD (MM)</b>	1428	<b>RIM ALT</b>	DW 16 L
<b>SLR (MM)</b>	638	<b>ECE</b>	E11-106R-002970
<b>RC (MM)</b>	4287	<b>SRI</b>	675

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6
50	2610	3060	3330	3555	3780	4005	4275	4500	-	-
40	2610	3060	3330	3555	3780	4005	4275	4500	-	-
30	2795	3275	3565	3805	4045	4290	4575	4815	-	-
25	2900	3400	3700	3950	4200	4450	4750	4995	-	-
10 CYC.	3175	3915	4255	4590	4995	5335	5670	6075	6415	6750
STATIC	4865	6005	6525	7040	7660	8180	8695	9315	9835	10350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.