


AW 711

| | |
|---------------------|--|
| TIRE SIZE | VF 480/45 R 17 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | COSECHADORA / MAQUINARIA AGRÍCOLA / COSECHADORA / MAQUINARIA AGRÍCOLA |
| VERSIÓN | STEEL BELTED |
| TIRE TYPE | TL |
| LI/SS | 167 A8/B |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CÓDIGO USA | 94051434 | RC (IN) | 104.1 |
| SW (IN) | 19.3 | RIM REC | 16.00 |
| OD (IN) | 34.1 | ECE | E4-106R-002652 |
| SLR (IN) | 14.3 | | |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 73 |
|-------------------------|------|------|------|------|------|------|------|------|-------|-------|
| FROM 5 TO 30 MPH | 3490 | 4450 | 5410 | 6130 | 7100 | 8060 | 8900 | 9730 | 10700 | 12010 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.