


# MULTIMAX MP 513

<b>TIRE SIZE</b>	<b>365/70 R 18 MPT</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	VÉHICULE UNIVERSEL / CAMION D'ENGRAIS / VÉHICULE UNIVERSEL
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	133 G



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	360	<b>RIM REC</b>	11
<b>OD (MM)</b>	969	<b>RIM ALT</b>	11 SDC; 12; 12 SDC
<b>SLR (MM)</b>	448	<b>ECE</b>	E11-54R-0016138
<b>RC (MM)</b>	2954	<b>SRI</b>	475

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.5	3.0	3.5	3.75
90	1080	1280	1520	1760	2000	2060
65	1170	1380	1650	1910	2170	2240
40	1250	1470	1750	2020	2300	2370

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.