


# AS 504

<b>TIRE SIZE</b>	<b>11.5/80 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	LEVANTADOR TELESCÓPICO / REBOQUE PARA OS CAMPOS / IMPLEMENTOS AGRÍCOLAS / LEVANTADOR TELESCÓPICO
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	126 A8
<b>LI/SS FREE ROLLING</b>	139 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	290	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	867	<b>ECE</b>	E11-106R-003510
<b>SLR (MM)</b>	380	<b>PR</b>	14
<b>RC (MM)</b>	2540	<b>SRI</b>	410

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.80
10 FR	3400
25 FR	2890
30 FR	2720
40 FR	2430
10 DW	2380
25 DW	2025
30 DW	1905
40 DW	1700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.